

Modelo CONJUNTO		S09P4S1	S12P4S1	S18P4S0	S24P4S2
Unidad Interior		SN09P4S1	SN12P4S1	SN18P4S0	SN24P4S0
Unidad Exterior		ST09P2	ST12P2	ST18P2	ST24P2
Imagen	Unidad				
Refrigeración					
Capacidad nominal (mín - máx)	W	2600(940~3300)	3400(1000~3770)	5200(1250~6000)	7020(1830~8000)
Consumo	W	825(240~1380)	1130(290~1500)	1597(330~2350)	2100(390~2900)
EER		3,15	3,01	3,25	3,34
SEER		6,1	6,1	6,5	6,5
Etiqueta energética		A++	A++	A++	A++
Calefacción					
Capacidad nominal (mín - máx)	W	2630(940~3360)	3420(1000~3810)	5300(1250~6200)	7100(1850~8000)
Consumo	W	767(240~1552)	1005(290~1720)	1403(340~2550)	1870(390~3200)
COP		3,42	3,4	3,77	3,79
SCOP		4,0	4,0	4,0	4,1
Etiqueta energética		A+	A+	A+	A+
Datos Unidad Interior					
Nivel de presión sonora ud. Interior	dB(A)	41/37/33/25/22	41/37/33/25/22	47/43/36/30/27	47/42/38/34/31
Nivel de presión sonora en modo Fresh air	dB(A)	/	/	/	/
Potencia sonora ud. Interior	dB(A)	51/47/43/35/32	51/47/43/35/32	56/53/46/39/37	58/52/48/44/41
Caudal de aire (refrigeración/calefacción)	m³/h	560/560	560/560	820/820	1100/1100
Capacidad de deshumidificación	L/h	1	1,2	1,8	2,5
Dimensiones (An x Al x Pr)	mm	790×275×192	790×275×192	920×306×195	1100×333×222
Dimensiones con embalaje (An x Al x Pr)	mm	860×345×265	860×345×265	990×380×265	1165×405×295
Peso neto	kg	8	8	10	14
Peso bruto	kg	10	10	12	17
Datos Unidad Exterior					
Caudal de aire	m³/h	1700	1700	2600	3000
Nivel de presión sonora	dB(A)	50	50	56	59
Potencia sonora	dB(A)	60	60	65	69
Dimensiones (An x Al x Pr)	mm	712×276×459	712×276×459	853×602×349	920×699×380
Dimensiones con embalaje (An x Al x Pr)	mm	765×481×310	765×481×310	890×628×385	960×732×430
Peso neto	kg	20	20	30	39
Peso bruto	kg	22	22	33	42
Datos Eléctricos					
Alimentación		220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P
Lado de alimentación		Exterior	Exterior	Exterior	Exterior
Corriente nominal (refrigeración)	A	4.0(1.2~8.0)	5.8(1.5~9.0)	7.0(1.5~12.0)	9.2(1.7~15.5)
Corriente nominal (calefacción)	A	3.8(1.2~9.0)	5.1(1.5~10.0)	6.3(1.6~13.0)	8.2(1.7~17.0)
Cable de conexión (hilos x tamaño)		4×0.75mm²	4×0.75mm²	4×0.75mm²	4×0.75mm²
Cable de alimentación (hilos x tamaño)		3×1.5mm²	3×1.5mm²	3×1.5mm²	3×2.5mm²
Datos frigoríficos					
Diámetro tubo de gas	pulg.	3/8"	3/8"	3/8"	1/2"
Diámetro tubo de líquido	pulg.	1/4"	1/4"	1/4"	1/4"
Refrigerante		R32	R32	R32	R32
Precarga de refrigerante / Distancia	kg / m	0.49 / 5	0.49 / 5	0.96 / 5	1.07 / 5
Carga adicional	g/m	15	15	25	25
Distancia máxima de tubería	m	25	25	25	25
Diferencia de altura máxima	m	10	10	10	10
Rango de funcionamiento					
Rango de operación	°C	16-31	16-31	16-31	16-31
Rango de funcionamiento (refrigeración)	°C	-15 ~ 53	-15 ~ 53	-15 ~ 53	-15 ~ 53
Rango de funcionamiento (calefacción)	°C	-25 ~ 30	-25 ~ 30	-25 ~ 30	-25 ~ 30